

AI NEXT

TECHNOLOGY · QUALITY · INNOVATION · VALUE

Intrusion Products



Emergency Panic Button



ESW-01

- ▶ Operating Voltage 250VDC
- ▶ Operating Current 300mA
- ▶ N/O and N/C Relay
- ▶ Auto Reset Mode

Indoor Dual PIR



DM-360

- ▶ Anti-glare protection
- ▶ Strong anti-interference
- ▶ Microwave detection
- ▶ High density detection area
- ▶ Intelligent temperature compensation
- ▶ Anti-tamper switch protection

Indoor PIR



DS-360

- ▶ Anti-glare protection
- ▶ Pet Immune
- ▶ High density detection area
- ▶ Intelligent temperature compensation
- ▶ Anti-tamper switch protection
- ▶ Strong RFI Immunity

Wireless Transmission Module



AS-100

- ▶ No wires. Clean installation
- ▶ Easy Installation with self adhesive tape or screws
- ▶ Compact, consumes very little power
- ▶ Micro-based signal activates
- ▶ Transmitter and Receiver Relay kit
- ▶ Compatible with all wired devices.

Pressure Sensor Mat



PSW2

- ▶ Waterproof
- ▶ Indoor/Outdoor Applications
- ▶ High Traffic Area Design
- ▶ Thermo Sealed
- ▶ Normally Open Switch

Mini Strobe Siren



SL-01BE

- ▶ Sounder – 108dB
- ▶ Flashes per minute – 150
- ▶ 12Vdc
- ▶ Current Draw 350mA
- ▶ Available in Red (Part #SL-01)

Request To Exit PIR

OD-22

The OD-22 passive infrared sensor is specifically designed for request-to-exit applications, includes qualified motion analysis. The sensor may be mounted to frame header, wall or ceiling. Intended for indoor use only.



- ▶ Relay Output
- ▶ Adjustable Relay 0.5-64 second time delay
- ▶ Micro-based signal processing
- ▶ 2 Form C Relay Output
- ▶ Dual voltage
- ▶ UL listed

Specifications:

OD-22

Supply Voltage	12-24VDC or VAC
Supply Current	18-30mA@12-24VDC,45-80mA@12-24VAC
Relay Output	2C Contact(N.C/N.O), 24VDC 1A Max.
Detection Type	Passive infrared
Relay Hold Time	0.5-64 seconds
LED Indication	Red
Range	Coverage 12x5 ft at 7ft high,30x12 ft at 15 ft high(Adjustment)
Operating Temp	-14° F to 131° F(-10° Cto55°C)
Weight	0. 4lb (0. 18kg)
Humidity	0-95% non-condensing
Dimensions	6.53"Wx1. 57"Hx1. 53"0 (166x40x39mm)

Design and specifications are subject to change without notice.



4700 AIRCENTER CIRCLE • RENO, NV 89502

PHONE: (775) 827-8000 • Fax: (775) 827-8044